

PERMABOND CODE: PB023 BLUE / PB129 WHITE

## LIQUID BONDING AGENT AND ADMIXTURE

DESCRIPTION: CROSSCO PERMABOND - is a plaster to concrete bonding agent ready to use that provides a permanent bond between structurally sound substrates and lime plaster. Creates a strong bond between old and new plaster and/or stucco. Improves the strength and performance of concrete when used as an admixture.

RECOMMENDEDRecommended for adhering plaster and/or stucco plaster to concrete, thus<br/>eliminating the need for costly mechanical means.

ADVANTAGES: •Fast Dry •Ready to Use •Non-Toxic •Excellent Bond •Water Clean-up •Creates Strong Bond

## **PRODUCT CHARACTERISTICS**

ColorAvailable Blue and White	Dry Time/Touch2 – 4 hrs
	Dry Time/Re-Coat4 hrs
Vehicle BasePVA	
	VOC<100 g/l
Weight/Gal9.05 lbs +/-	
	PH7.7
Solids/Weight28% +/- 1%	
N// // 05 440	Flash PointNon-Flammable
Viscocity95 - 110	Application town FF 00% F
Odor <u>Clicht</u>	Application temp55 – 90° F
OdorSlight	Tool Cloopup Water
	Tool CleanupWater

APPLICATIONApply each coat at a suggested rate of 1 Gal per 350 sq. ft. Refer to systemRATE:specifications for more details.





## PERMABOND

GENERAL PRODUCT INFORMATION		
SYSTEM SPECIFICATIONS	APPLICATION LIMITATIONS	
PermaBond is ready to use. Apply a uniform of bonding agent to existing surface with brush, or airless spray. Make sure all areas are covered with product. After application, allow 4 hours to dry before applying plaster/stuck surface. Trowel on plaster/stucco on a cin motion. If product is left on surface longer the hours, an additional coat is required.	roller forecast. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM co to FREEZING. rcular	
Shelf Life: 12 months when stored at room	SAFETY INFORMATION	
temperature unopened.	Refer to product Material Safety Data Sheet (MSDS) prior to product use.	
SURFACE PREPARATION	PRECAUTIONS	
Remove all dirt, dust loose or flaking rust. Use bleach solution with water to remove any milde algae, or mold from surface. Surface must be p washed to remove dirt, loose paint, excess rust other foreign matter which could prevent prope adhesion. Surface must be completely dried be applying coating. NOTE: This product has excellent suspension an requires minimal stirring. Do Not Thin.	ew, grade use only. Dispose of container after use. HARMFUL if swallowed. For exterior use only, use in well ventilated area. Keep out of reach of children. er efore <u>Notice</u> : The technical data contained herein are true and accurate to the best of our knowledge.	
AVAILABLILITY		
PB023 BLUE PB129 WHITE		
PBXXX-0 250 Gal Tote		
PBXXX-1 55 Gal Dr PBXXX-2 5 Gal PL		
PBXXX-2 5 Gal PL PBXXX-4 4/ 1 Gal		

