

SPOTLESS TIRE SHINE

CODE: AT010

DESCRIPTION: SPOTLESS TIRE SHINE – was formulated using the best technologies of polymers and high molecular silicones providing a deeper, longer lasting shine. Protects and leaves tires looking like new with a wet/black shine even under the most extreme weather conditions. Just Spray and Go!

RECOMMENDED USES: SPOTLESS TIRE SHINE was designed to protect and beautify all type of rubber tires. Our high gloss formula gives your tires a "wet-look" with a dark shine. Highly water-resistant polymers combined with anti-ozonant technology keep tires looking blacker longer, while preventing cracking, browning, and premature aging. Excellent to use on vinyl tops, bumpers and rubber trims.

DESCRIPTION:

•100% Silicone Formula	•Protects & Shines
•High Gloss Formula	•No Overspray
•Anti-Corrosive	•Streak Free Formula

PRODUCT CHARACTERISTICS

Odor, Color.....Light Solvent, Clear	Boiling Point.....>355° F (initial)
Vehicle Base.....Silicone Polymers	Density.....1.035-1.045 g/ml
Weight/Gal.....8.5 lbs	VOC.....<10 g/l
Solubility in Water...Negligible	PH.....None – Solvent Base
Solids by Weight.....25% +/- 1%	Vapor Density(air=1)...5.3

SPOTLESS TIRE SHINE
CODE: AT010

TIRE SHINE

GENERAL PRODUCT INFORMATION

INSTRUCTIONS

Spray onto dry tire surface. Hold bottle 4" – 6" from tire. Allow to dry. Spotless Tire Shine is a self-leveling formula. Tires may be wiped after product sets for 3 to 5 minutes. Repeat applications for maximum shine.

CAUTION

Caution: Do not take internally. Keep out of reach of children. Use only with adequate ventilation. Product must be used within one year of purchase. Avoid contact with eyes, skin and clothing. Wear protective eyewear, gloves and footwear when handling. Avoid breathing of vapors. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage.

Refer to product Material Safety Data Sheet (MSDS) prior to product use.

For chemical emergency only, call Chemtrec 1- 800-424-9300

SAFETY INFORMATION

COMBUSTIBLE! Keep from heat, sparks, or open flame.

Refer to product Material Safety Data Sheet (MSDS) prior to product use.

Notice: The technical data contained herein are true and accurate to the best of our knowledge.

Published instructions are subject to change without prior notice.

AVAILABILITY

AT010-1	55 Gal PL
AT010-2	5 Gal PL
AT010-4	4/ 1 Gal
AT010-5	12/ QT