

CROSSHINE
CODE: CK223

DESCRIPTION: CROSSCO – CROSSHINE (3th step) protects and embellishes all type of floors, leaving perfect finishing for terrazzo, ceramic, cork, wood, linoleum, vinyl, rubber, asphalt and floors of parquet. An excellent product for damp mopping and spray buffing with any speed buffing machine. Dries to a hard durable finish.

RECOMMENDED USES: CROSSCO – CROSSHINE is excellent for use on Vinyl, Vinyl Composition, Asphalt, Rubber, Concrete, Flagstone, Brick, Terrazzo, Sealed Wood floors. Designed for low or high maintenance floor care programs.

ADVANTAGES:

- High gloss finish
- Moderate to high traffic coat
- Could be used without sealer
- Self leveling
- Detergent resistant
- Easy to apply

PRODUCT CHARACTERISTICS

Solids.....	18.0 ± 0.5%	Dry/Recoat time.....	30 min
Color.....	Milky White	Detergency	Excellent
Odor.....	Mild	Waterspot Resistance.....	Excellent
pH	8.5 – 9	VOC.....	0.31 lbs/gal
Viscosity	Water thin	Coverage.....	2500 s.f./gal +/-
Gloss	90+ specular	Storage/Stability	2 years
Leveling	Excellent	Weight per Gallon	8.90 lbs./gal.
Buffabiliyu	Spray Buff or Restorer	Freeze / Thaw Stability ..	Keep from freezing

CROSSHINE

GENERAL PRODUCT INFORMATION

FOR USE	SAFETY INFORMATION								
<ul style="list-style-type: none"> - Vinyl Tile - Asphalt Tile - Rubber Tile - Flagstone - Ceramic Tile <ul style="list-style-type: none"> - Vinyl Asbestos - Linoleum - Concrete - Terrazzo 	<p>Avoid contact with eyes, skin and clothing. Wear protective eyewear, gloves and footwear when handling. Avoid breathing of vapors. Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only.</p>								
DIRECTIONS									
<p>PREPARATION: If stripping is necessary, use <i>CROSSCO WAXEX stripper</i> and follow directions accordingly.</p> <p>If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.</p> <p>FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.</p> <p>MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.</p>	<p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p> <p>For chemical emergency only, call Chemtrec 1- 800-424-9300</p> <p>Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published instructions are subject to change without prior notice.</p>								
	AVAILABILITY								
	<table border="0"> <tr> <td>CK223-1</td> <td>55 GAL</td> </tr> <tr> <td>CK223-2</td> <td>5 GAL</td> </tr> <tr> <td>CK223-4</td> <td>4/ 1 GAL</td> </tr> <tr> <td>CK223-5</td> <td>12/ 32oz Bottle</td> </tr> </table>	CK223-1	55 GAL	CK223-2	5 GAL	CK223-4	4/ 1 GAL	CK223-5	12/ 32oz Bottle
CK223-1	55 GAL								
CK223-2	5 GAL								
CK223-4	4/ 1 GAL								
CK223-5	12/ 32oz Bottle								