

**DP SEAL**  
CODE: DP081

**DESCRIPTION:** CROSSCO DP-SEAL (2<sup>ND</sup> Step) was developed to be used on all type of floors with heavy traffic. Use DP Seal to seal porous and mistreated floors before applying CROSSCO Cromkote or CROSSCO Crossshine. It provides an extra acrylic base coat before desired floor finish.

**RECOMMENDED USES:** CROSSCO DP-SEAL Can be used on all resilient and non-resilient flooring as well as wood, cork, concrete, terrazzo and "no wax" floors. Excellent for use on Vinyl, Vinyl Composition, Asphalt, Rubber, Concrete, Flagstone, Brick, Terrazzo, Sealed Wood floors.

**ADVANTAGES:**

- One Coat Performance
- Stain Resistance
- Detergent Resistant
- Diamond Tough Durability
- Slip Resistance
- Easy to apply

**PRODUCT CHARACTERISTICS**

Solids.....	10.0 ± 0.5%	Dry/Recoat time.....	30 min
Color.....	Milky White	Detergency .....	Excellent
Odor.....	Mild	VOC.....	0.35 lbs/gal
pH .....	8.0 – 9.0	Storage/Stability .....	1 years
Viscosity .....	Water thin	Weight per Gallon .....	9.15 lbs./gal.
Leveling .....	Excellent	Freeze / Thaw Stability ..	Keep from freezing

**GENERAL PRODUCT INFORMATION**

FOR USE	SAFETY INFORMATION							
<ul style="list-style-type: none"> <li>- Vinyl Tile</li> <li>- Asphalt Tile</li> <li>- Rubber Tile</li> <li>- Flagstone</li> <li>- Ceramic Tile</li> </ul> <ul style="list-style-type: none"> <li>- Vinyl Asbestos</li> <li>- Linoleum</li> <li>- Concrete</li> <li>- Terrazzo</li> </ul>	<p>Avoid contact with eyes, skin and clothing. Wear protective eyewear, gloves and footwear when handling. Avoid breathing of vapors. Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only.</p>							
DIRECTIONS	<p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p> <p>For chemical emergency only, call Chemtrec 1- 800-424-9300</p>							
<p><u>New Application:</u></p> <ul style="list-style-type: none"> <li>-Strip all old finish from floor using <i>CROSSCO WAXEX Stripper</i>. Rinse well with cold water until no residue remains, and allow floor to dry thoroughly.</li> <li>-Once floor is stripped and dust free, apply a coat of <i>CROSSCO DP-SEAL Floor Sealer</i> to seal porous condition created by the stripper.</li> <li>-Minimum application temperature is 50°F.</li> <li>- Coverage on very porous substrates; i.e. concrete, terrazzo, 500-1200 sq. ft./gal. Less porous substrates; i.e. composition vinyl tile, 1000-2000 sq. ft./gallon.</li> </ul>								
	AVAILABILITY							
	<table border="0"> <tr> <td>DP081-1</td> <td>55 GAL</td> </tr> <tr> <td>DP081-2</td> <td>5 GAL</td> </tr> <tr> <td>DP081-4</td> <td>4/ 1 GAL</td> </tr> <tr> <td>DP081-5</td> <td>12/ 32oz Bottle</td> </tr> </table>	DP081-1	55 GAL	DP081-2	5 GAL	DP081-4	4/ 1 GAL	DP081-5
DP081-1	55 GAL							
DP081-2	5 GAL							
DP081-4	4/ 1 GAL							
DP081-5	12/ 32oz Bottle							
	WARRANTY							
	<p>Max Chemical, Inc. warrant only that this product is free of defects, since many factors which affects the results obtained from this product (such as weather, workmanship, equipment used and prior conditions of substrate) are beyond our control. We will replace at no charge any product proven to be defective within 90 days of purchase, provided it has been applied as manufacturer's specifications.</p>							