

FLOOR TILE ADHESIVE

CODE: AD007

DESCRIPTION:

CROSSCO Floor Tile Adhesive is a water resistant and strong multi-purpose adhesive for the installation of interior floor covering materials. This formula allows adjustments of the flooring materials being laid after it is applied, before setting rapidly to a permanent type bond.

RECOMMENDED USES:

Our Floor Tile Adhesive is specially designed for the installation of interior floor covering materials such as vinyl, vinyl asphalt, carpet tiles, sponged backed vinyl sheet goods and indoor carpeting.

DESCRIPTION:

- Ready to Use
- Non-Flammable
- Smooth spreadability
- White Color
- Strong Bond
- Water Clean up

PRODUCT CHARACTERISTICS

Color.....Light Bone	Dry Time.....20 min
Vehicle Base.....Latex	Set-Up.....2 hrs
	Total Cure.....24 hrs
Weight/Gal.....11.70 lbs	VOC.....<100 g/l
Solids/Weight..... 60 +/- 1%	PH.....8 - 9
Solids Volume..... 48 +/- 1%	Flash Point.....None
Viscosity.....400,000 cps	Clean Up.....Water

APPLICATION RATE:

Apply at a suggested rate of 1 Gal per 200 sq. ft. Refer to system specifications for more details.

FLOOR TILE ADHESIVE CODE: AD007

MULTIPURPOSE FLOORING ADHESIVE

GENERAL PRODUCT INFORMATION

SYSTEM SPECIFICATIONS	NOTE						
<p>Spread adhesive evenly with a notched trowel. For rubber, plastic floor tile and linoleum, use a notched trowel of 1/16" x 1/16" x 1/16". For vinyl and vinyl asbestos floor tile -light gauge, use a notched trowel of 1/32" x 1/16" x 1/32".</p> <p>Set tiles or lay flooring within twenty minutes after application, leaving no bare spots.</p> <p>Roll installed resilient tiles immediately with a floor roller. Before setting vinyl tile let adhesive get slightly tacky.</p>	<p>New concrete must be dry and fully cured for six months before applying adhesive. Do not use where excess moisture, vapor or alkali conditions exist through concrete floors. One check for moisture content in concrete is to tape an asphalt tile on the floor sealing all edges. After 48 hours, remove and examine the backside for moisture condensation and inspect the concrete surfaces for darkened areas. The source of moisture, if present, must be located, and the cause must be corrected prior to adhesive application.</p>						
SURFACE PREPARATION	CAUTION						
<p>Remove all dirt, dust loose or flaking rust. Use mild bleach solution with water to remove any mildew, algae, or mold from surface. Surface must be power washed to remove dirt, loose paint, excess rust, and other foreign matter which could prevent proper adhesion. Surface must be completely dried before applying coating.</p> <p>NOTE: This product has excellent suspension and requires minimal stirring. Do Not Thin.</p>	<p>Caution: Do not take internally. Close container after each use. Keep out of reach of children. Use only with adequate ventilation. Product must be used within one year of purchase.</p>						
APPLICATION LIMITATIONS	LIMITATIONS						
<p>Do not apply below 50° F (10°C) or when rain is forecast. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM FREEZING.</p>	<p>Do not use bellow grade. Do not use if excess moisture vapor or alkali conditions exist through concrete floors.</p>						
	AVAILABILITY						
	<table border="0"> <tr> <td>AD007-2</td> <td>5 Gal PL</td> </tr> <tr> <td>AD007-4</td> <td>4/ 1 Gal</td> </tr> <tr> <td>AD007-5</td> <td>12/ QT</td> </tr> </table>	AD007-2	5 Gal PL	AD007-4	4/ 1 Gal	AD007-5	12/ QT
AD007-2	5 Gal PL						
AD007-4	4/ 1 Gal						
AD007-5	12/ QT						
	SAFETY INFORMATION						
	<p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p>						