

WALL PAPER ADHESIVE

CODE: AD009

DESCRIPTION: CROSSCO WALLPAPER ADHESIVE - Universal Wallpaper paste makes hanging wallpaper easy. Non-staining, non-flammable, non-bleeding, ready to use adhesive, suitable for hanging all types of vinyl wall coverings, wallpaper, papers or cloth backed fabrics. This paste may be used on all surfaces except for poor quality latex paint.

RECOMMENDED USES: Our Wallpaper Adhesive is specially designed for the installation vinyl wall coverings, wallpaper, papers or cloth backed fabrics. For hanging over wallcovering or painted surfaces. Not Recommended For: Bare Drywall, extremely rough surfaces such as concrete block, stucco, and other rough surfaces.

- DESCRIPTION:**
- Ready to Use
 - Longer Open Time
 - Non-Flammable
 - Strong Bond
 - For All Wallpapers
 - Water Clean up

PRODUCT CHARACTERISTICS

Color.....White	Dry Time.....20 min
	Total Cure.....24 hrs
Vehicle Base..... Synthetic Polymer	VOC.....<200 g/l
Weight/Gal.....11.70 lbs	PH.....8 - 9
Solids/Weight..... 12 +/- 1%	Flash Point.....None
Solids Volume..... 8 +/- 1%	Clean Up.....Water
Viscosity.....14,000 cps	

APPLICATION RATE: Apply at a suggested rate of 1 Gal per 250 sq. ft. Refer to system specifications for more details.

WALL PAPER ADHESIVE CODE: AD009

MULTIPURPOSE FLOORING ADHESIVE

GENERAL PRODUCT INFORMATION

SURFACE PREPARATION

CAUTION

Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for loose wallcoverings. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier. To check for poor quality latex paint, cut an "x" in the wall and apply clear tape over it. Remove quickly, if there is paint on the tape, you need to prime with Crossco Wall Primer.

Caution: Do not take internally. Close container after each use. Keep out of reach of children. Use only with adequate ventilation. Product must be used within one year of purchase.

LIMITATIONS

Do not use bellow grade. Do not use if excess moisture vapor or alkali conditions exist through walls.

SYSTEM SPECIFICATIONS

AVAILABILITY

Apply even coat to wall paper with a roller or brush. Adhere paper to desire wall surface and press firmly with application bristle brush.

AD009-2	5 Gal PL
AD009-4	4/ 1 Gal
AD009-5	12/ QT

Drying Time: Drying time between two vinyls will vary depending on the temperature, ventilation and humidity of the room.

Clean-Up: Before the paste dries, remove excess with warm, clean water. Additional effort may be required if the paste is allowed to contact the surface of embossed or textured vinyls. Paste can be difficult to clean up after it is dry.

Tinting: N/A

Dilution: Do not dilute.

SAFETY INFORMATION

Refer to product Material Safety Data Sheet (MSDS) prior to product use.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published instructions are subject to change without prior notice.

APPLICATION LIMITATIONS

Do not apply below 50° F (10°C) or when rain is forecast. Low temperatures and high humidity will prolong coat dry time. KEEP FROM FREEZING.