

**ES2000 PRIMER**  
CODE: RS060

**ACRYLIC ROOF & WALL PRIMER SEALER**

**PRODUCT DESCRIPTION:** CROSSCO ES2000 PPRIMER is a styrene acrylic ultra violet stable resin membrane formulated to conform to the highest standards of impermeability that the modern technology allow us. This primer penetrates material's porosity, guarantying unmatched substrate adhesion and unequaled waterproofing properties.

**RECOMMENDED USES:** CROSSCO ES2000 PRIMER is excellent for waterproofing concrete roofs, concrete, masonry, stucco, wood surfaces, painted or primed aluminum/metal roof decks or siding.

- ADVANTAGES:**
- Seals & Cures concrete
  - Stays Tacky for Best Adhesion
  - Dries Clear
  - Ready to Use
  - Penetrates & Seals
  - Fast Dry

### PRODUCT CHARACTERISTICS

Color.....Milky White Dries Clear	Dry Time/Touch.....60 min
Vehicle Base.....Styrene Acrylic	Dry Time/Re-Coat.....24 hrs
Weight/Gal.....8.7 lbs	VOC.....<100 g/l
Solids/Weight.....25% +/- 2%	PH.....7.0 – 8.0
Viscosity.....Liquid	Flash Point.....Non-Flammable
	Thinning.....Ready to Use

**APPLICATION RATE:** Apply each coat at a suggested rate of 1 Gal per 125 sq. ft. Refer to system specifications for more details.

ES2000 PRIMER

## GENERAL PRODUCT INFORMATION

SYSTEM SPECIFICATIONS	APPLICATION LIMITATIONS					
<p>Apply a heavy coat with: 1-BRUSH: Use a good quality nylon or polyester brush. 2-ROLLER: Use a 3/4" Nap Rough Surface Roller. Let product dry four hours before applying a Top Coat. Mixing: Always mix thoroughly with a powerful agitator before application.</p>	<p>Do not apply below 50° F (10°C) or when rain is forecasted. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM FREEZING.</p>					
	<p style="text-align: center;"><b>AVAILABILITY</b></p> <table border="1" data-bbox="714 821 1420 989"> <tr> <td>RS060-1</td> <td>55 Gal Dr</td> </tr> <tr> <td>RS060-2</td> <td>5 Gal PL</td> </tr> <tr> <td>RS060-4</td> <td>4/ 1 Gal</td> </tr> </table>	RS060-1	55 Gal Dr	RS060-2	5 Gal PL	RS060-4
RS060-1	55 Gal Dr					
RS060-2	5 Gal PL					
RS060-4	4/ 1 Gal					
SURFACE PREPARATION						
<p>Remove all dirt, dust loose or flaking rust. Use mild bleach solution with water to remove any mildew, algae, or mold from surface. Surface must be power washed to remove dirt, loose paint, excess rust, and other foreign matter which could prevent proper adhesion. Surface must be completely dried before coating is applied.</p> <p>NOTE: This product has excellent suspension and requires minimal stirring. Do Not Thin.</p>	SAFETY INFORMATION					
	<p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p>					
	CLEAN UP					
	<p>Clean brushes and tools immediately after use with warm soapy water. Completely flush all spray equipment with this solution.</p>					
PONDING WATER	WARRANTY					
<p><b>IMPORTANT:</b> Even though this product helps protect against water ponding conditions, roof drains or other corrective measures must be installed to eliminate water build-ups prior to coating the roof.</p>	<p>Max Chemical, Inc. warrant only that this product is free of defects, since many factors which affects the results obtained from this product (such as weather, workmanship, equipment used and prior conditions of substrate) are beyond our control.</p>					