

OVEN CLEANER & DEGREASER

GRS-500 CODE: DE075

DESCRIPTION: CROSSCO GRS-500 is specially formulated to cut through grease build-up in

ovens, range hoods, fryers, grills, kitchen hoods and other stainless steel equipment. Powerful cleaner removes carbon buildup, cooking deposits, and burnt-on grease deposits from most commercial kitchen cooking surfaces

(not for use on aluminum or painted surfaces).

RECOMMENDED

USES:

CROSSCO GRS-500 - Cleans fyers, ovens, grills, exhaust hoods, fans, ranges, racks, panels, etc. Safe on stainless steel, cast iron, chrome, brass, copper,

porcelain, glass, and glazed brick

ADVANTAGES: •Tough on Grease Build-up

•Non-Streak Formula

Ready to use

Fast Acting Formula

•Rinses Away

•Industrial Strength

PRODUCT CHARACTERISTICS

Odor, Color.....Light, Clear Specific Gravity.......1.01

Physical State.......5% g/l

Weight/Gal......9.5 lbs PH......10-11

Viscocity......Not Flammable

Solubility in Water...Complete Boiling Point.... 200 – 290°F



GRS-500 CODE: DE075

OVEN CLEANER & DEGREASER

GENERAL F	PRODUCT	INFORMATION
------------------	---------	-------------

INSTRUCTIONS	SAFETY INFORMATION
Full Strength: use directly to surface when heavy deposits present. Apply with sprayer or brush and let stand for 15-25 minutes. Flush with warm water. Steel wool might be required to remove deep stains.	EMERGENCY OVERVIEW: DANGER! CORROSIVE. Can cause burns to the respiratory tract, skin, eyes and gastrointestinal tract. Can cause permanent eye damage. May be harmful or fatal if swallowed. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist. Wash thoroughly after handling. Mixing with water, acid or incompatible materials may cause splattering and release of heat EYE CONTACT: Can cause severe irritation, corrosion, and damage to eyes. SKIN CONTACT: Can cause severe irritation and corrosion of tissue. INHALATION: Prolonged exposure can cause severe irritation, possible burns with pulmonary edema. INGESTION: Can cause irritation, corrosion/ulceration, nausea, and vomiting. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory system (including asthma and other breathing disorders). GET MEDICAL ATTENTION IMMEDIATELY. Refer to product Material Safety Data Sheet (MSDS)
Dilute 1:1: for regular cleaning and light deposits dilute with equal part of water. Apply with sprayer or brush and let stand for 15-25 minutes. Flush with warm water.	
Do Not Use on aluminum, painted surfaces, plastic laminate counter tops, iron surfaces.	
CAUTION	
Caution: Do not take internally. Close container after each use. Keep out of reach of children. Use only with adequate ventilation. Product must be used within one year of purchase.	
AVAILABLILITY	prior to product use.
DE075-1 55 Gal PL DE075-2 5 Gal PL DE075-4 4/ 1 Gal DE075-5 12/ QT	Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published instructions are subject to change without prior notice.