

**PERMA SEAL ACRILICO**

CODE: RS026

**PRODUCT DESCRIPTION:** CROSSCO PERMA SEAL ACRILICO is a roof and walls sealer with a white finish, reinforced with silicone and acrylic, providing a strong reflective layer that protects the roof surface. The white finish reflects the UV rays and reduce the internal temperature protecting the surface. Water base technology makes it easy to clean and low odor.

**RECOMMENDED USES:** For protecting and waterproofing a wide assortment of roofing substrates that are structurally sound. The brilliant white finish contributes significantly to reduce temperature by reflecting solar rays.

- ADVANTAGES:**
- Ultra White
  - Reflects Sun’s Heat Rays
  - Lowers Interior Temperature
  - Seals and Protects
  - Fiber Reinforced
  - Water Clean Up

**PRODUCT CHARACTERISTICS**

Color.....White	Dry Time/Touch.....1 hr
Vehicle Base.....Polyvinyl	Dry Time/Re-Coat.....24 hrs
Weight/Gal.....10.5 lbs	VOC.....<100 g/l
Solids/Weight.....>48%	PH.....7-8
Solids Volume.....>42%	Flash Point.....Non-Flammable
Viscosity.....115-120 kus	Elongation.....>100%

**APPLICATION RATE:** Apply each coat at a suggested rate of 1 Gal per 50-60 sq. ft. Refer to system specifications for more details.

PERMA SEAL ACRILICO  
CODE: RS026

### GENERAL PRODUCT INFORMATION

SYSTEM SPECIFICATIONS	PONDING WATER		
<p style="text-align: center;"><i>Metal</i></p> <p>Apply 1<sup>st</sup> Coat at a rate of 1 gallon per 100 sq.ft. Apply 2<sup>nd</sup> Coat at a rate of 1 gallon per 50 sq.ft.</p> <p style="text-align: center;"><i>Single Ply – Mod. Bitumen -</i></p> <p>Apply 1<sup>st</sup> Coat at a rate of 1 gallon per 100 sq.ft. Apply 2<sup>nd</sup> Coat at a rate of 1 gallon per 50 sq.ft.</p> <p style="text-align: center;"><i>Concrete – Wood - Polyurethane Foam</i></p> <p>Apply 1<sup>st</sup> Coat at a rate of 1 gallon per 50 sq.ft. Apply 2<sup>nd</sup> Coat at a rate of 1 gallon per 50 sq.ft.</p>	<p><b>IMPORTANT:</b> Where water ponding conditions exists, roof drains or other corrective measures must be installed to eliminate water build-ups prior to coating the roof.</p> <tr> <th data-bbox="711 703 1425 767">APPLICATION LIMITATIONS</th> <td data-bbox="711 767 1425 996"> <p>Do not apply below 50° F (10°C) or when rain is forecasted. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM FREEZING.</p> </td> </tr>	APPLICATION LIMITATIONS	<p>Do not apply below 50° F (10°C) or when rain is forecasted. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM FREEZING.</p>
APPLICATION LIMITATIONS	<p>Do not apply below 50° F (10°C) or when rain is forecasted. Low temperatures and high humidity will prolong coat dry time. Allow 4 +/- hours for coating to dry prior to being subjected to rain. KEEP FROM FREEZING.</p>		

### SURFACE PREPARATION

### AVAILABILITY

Remove all dirt, dust loose or flaking rust. Use mild bleach solution with water to remove any mildew, algae, or mold from surface. Surface must be power washed to remove dirt, loose paint, excess rust, and other foreign matter which could prevent proper adhesion. Surface must be completely dried before applying coating.  
NOTE: This product has excellent suspension and requires minimal stirring. Do Not Thin.

RS026-0	250 Gal Tote
RS026-1	55 Gal Dr
RS026-2	5 Gal PL

### SAFETY INFORMATION

Refer to product Material Safety Data Sheet (MSDS) prior to product use.

### WARRANTY

Max Chemical, Inc. warrant only that this product is free of defects, since many factors which affects the results obtained from this product (such as weather, workmanship, equipment used and prior conditions of substrate) are beyond our control.

### CLEAN UP

Clean brushes and tools immediately after use with warm soapy water. Completely flush all spray equipment with this solution.