

SPRAY BUFF

CODE: CK035

DESCRIPTION: CROSSCO – SPRAY BUFF is a restoration polymeric treatment that enhances the brilliance of floor finishes in a spray buff program. Formulated with acrylic copolymers, this product produces a clean, slip-resistant, glossy finish on all resilient and composition floors. Dries to a hard durable finish.

RECOMMENDED USES: CROSSCO – SPRAY BUFF is Ideal for use in any floor repair that requires spray buffing, UHS burnishing or auto scrubbing. Designed to reduce mop and machine drag, plus formulated to be compatible with most floor finishes.

- ADVANTAGES:**
- Brilliant Reflective Shine
 - Slip Resistance
 - UHS Compatible
 - Detergent Blended
 - Self leveling Ability
 - Easy to apply

PRODUCT CHARACTERISTICS

Solids.....	11.0 ± 0.5%	Dry/Recoat time.....	30-40 min
Color.....	Milky White	Detergency	Excellent
Odor.....	Mild	Waterspot Resistance.....	Excellent
pH	8.5 – 9	VOC.....	<0.10 lbs/gal
Viscosity	Water thin	Storage/Stability	1 years
Gloss	90+ specular	Weight per Gallon	8.35 lbs./gal.
Leveling	Excellent	Freeze / Thaw Stability ..	Keep from freezing

GENERAL PRODUCT INFORMATION

FOR USE	SAFETY INFORMATION							
<p>Building Service Contractors • Hospitals • Nursing Homes • Office Buildings • Airports • Hotels/Motels • Supermarkets • Department Stores</p>	<p>Avoid contact with eyes, skin and clothing. Wear protective eyewear, gloves and footwear when handling. Avoid breathing of vapors. Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only.</p> <p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p> <p>For chemical emergency only, call Chemtrec 1- 800-424-9300</p>							
DIRECTIONS								
<p>-Use on any floor repair that requires spray buffing, UHS burnishing, or auto scrubbing.</p> <p>-Always dilute SPRAY BUFF properly and use approved protective equipment: -Dilute 42 oz. per gallon of cold water for spray buffs. -Dilute 3-6 oz. per gallon as a restorer. -Dilute 2-3 oz. per gallon as a cleaner.</p> <p>-Apply SPRAY BUFF to floor surfaces using thin coats and a clean mops with a spray bottle or an auto scrubber. (Product will dry to a dull haze and will restore gloss after burnishing when used as a mop-on restorer.)</p> <p>-If using an auto scrubber, SPRAY BUFF should be diluted properly in the solution tank. Scrub floor and allow to dry to touch before high-speed burnishing. Product may dry to a dull haze but will restore to a high gloss after burnishing.</p>	AVAILABILITY							
	<table border="0"> <tr> <td>CK035-1</td> <td>55 GAL</td> </tr> <tr> <td>CK035-2</td> <td>5 GAL</td> </tr> <tr> <td>CK035-4</td> <td>4/ 1 GAL</td> </tr> <tr> <td>CK035-5</td> <td>12/ 32oz Bottle</td> </tr> </table>	CK035-1	55 GAL	CK035-2	5 GAL	CK035-4	4/ 1 GAL	CK035-5
CK035-1	55 GAL							
CK035-2	5 GAL							
CK035-4	4/ 1 GAL							
CK035-5	12/ 32oz Bottle							
<th data-bbox="711 1335 1425 1400">WARRANTY</th>	WARRANTY							
<p>Max Chemical, Inc. warrant only that this product is free of defects, since many factors which affects the results obtained from this product (such as weather, workmanship, equipment used and prior conditions of substrate) are beyond our control. We will replace at no charge any product proven to be defective within 90 days of purchase, provided it has been applied as manufacturer's specifications.</p>								